



XINXIANG KOLANKY

The leader of oilfield drilling
and cementing chemicals

Cement Spacer KOL SP CEM

PROPERTY

KOL SP CEM is a dusting agent that made of some high active surface active agents, suspending agent weighting agent thinner and the others addition agents.

BASIC DATA

Appearance	Fineness	Temperature Renge
Free flow powder or granule	≤ 10.0 (0.425mm sieve residue) , %	25~150°C (BHCT)

TECHNICAL DATA

Items	Specification	Cement slurry formulations
Moisture content, %	≤ 10.0	G cement, W/C: 0.44 Water quality: tap water. Sample dosage: 5% SP (BWOC)
Initial consistency , Bc	≤ 30	
Thickening time , min/80°C .46.5Mpa.45min	≥ 60	
Density difference, g/cm ³	≤ 0.05	
Compression strength, Mpa/80°C . normal pressure.24h	≥ 7	

FEATURE

It can be formulated in a different proportion of release agent on request, 1.0 ~ 1.9g / cm³

It's non-toxic, odorless, non-corrosive.

It is formulated isolation solution can effectively replace, washing mud, cement slurry and mud to prevent cross-contamination.

Formulated spacer fluid and the cement slurry has good compatibility, can effectively dilute slurry and improve performance.

PACKAGE & STORAGE

Sacked with three packages, 25kg/sack .

Be kept away from moisture and possible damage of the packages in transportation .Storage life is two years.

Tel: 86-373-5270048
Email: info@oilfield-chem.com
Web: www.oilfield-chem.com